#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization International Bureau



### 

### (43) International Publication Date 29 March 2001 (29.03.2001)

#### **PCT**

# (10) International Publication Number WO 01/21888 A1

(51) International Patent Classification7:

\_\_\_\_

(21) International Application Number: PC

PCT/FI00/00817

D21G 1/00

(22) International Filing Date:

22 September 2000 (22.09.2000)

(25) Filing Language:

Finnish

(26) Publication Language:

English

(30) Priority Data: 19992058

24 September 1999 (24.09.1999) FI


- (71) Applicant (for all designated States except US): VALMET CORPORATION [FI/FI]; Fabianinkatu 9 A, FIN-00130 Helsinki (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): LEPPÄKOSKI, Helena [FI/FI]; Sirukuja 6, FIN-04440 Järvenpää (FI).

KOIVUKUNNAS, Pekka [FI/FI]; Tupalantie 13 D 31, FIN-04400 Järvenpää (FI). HASANEN, Kari [FI/FI]; Päivärinteentie 13 A 6, FIN-04250 Kerava (FI).

- (74) Agent: SEPPO LAINE OY; Itämerenkatu 3 B, FIN-00180 Helsinki (FI).
- (81) Designated States (national): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: METHOD AND ASSEMBLY FOR OPENING CALENDER NIPS



(57) Abstract: The present invention relates to a method and assembly for opening the nips (9, 10) of a calender comprising at least two elements (1, 2; 3, 4) brought to a nip contact with each other, especially for performing the nip opening at a break or damage occurring in the web (5) being calendered. The tension of the web (5) being calendered is measured at multiple points over the cross-machine width of the web (5) and the calender nips (9, 10) are opened when the measured web tension at a preset number of points over the cross-machine width of the web (5) has fallen to a limit value that by a decision-making algorithm monitoring the tension profile of the web (5) is interpreted to indicate a web break situation or other damage on the web (5) requiring opening the nips (9, 10).

/O 01/21888